



Flat CFDK 25 capacitive sensor with versatile mounting options

- Versatile mounting options
- Space-saving installation
- Snap-in/snap-out without tools

Snap-in without tools

Removable containers can be replaced while the sensor stays

The sensor can comfortably be added after an easy subassembly

of the frame





snap in the sensor



cascaded and screwed onto

the wall behind a tank

and ready!


CFDK 25 – Space-saving plug-and-play solution


The sensor with only 6 mm installation height is suitable for all applications where space is a critical factor.

Mounted directly onto tanks, it detects fill levels of liquids. Countersunk flush beneath a conveyor band it can detect objects on it.

Various fixed sensing distances of 2 to 15 mm turn the CFDK 25 into a plug-and-play solution.

Versatile mounting options...





on a tank with Velcro fastener

or glued


on a standpipe with cable ties

Product overview

Product code	Sensing distance	Mounting type	Designed for
CFDK 25G1125/LN1	2 mm	Shielded	Film-forming liquids with high dielectric constant
CFDK 25G1125/LN3	4 mm	Shielded	Hydrous liquids and media with low dielectric constant
CFDK 25G1125/LN5	12 mm	Shielded	Object detection under very confined installation conditions
CFDK 25G1125/LN6	15 mm	Unshielded	Detection of imprecisely positioned objects
HC25-1 Assembly frame			Fixation, quick (dis-)assembly


Dimensional drawing


Sensor



screwed in place flush beneath a conveyor belt

Assembly frame





Technical data		
Housing material	PA12	
Operating temperature	-25 +75 °C	
Connection types	PVC cable / M8 flylead connector	
Protection class	IP 65	

For more information visit www.baumer.com/news/551

Baumer

Baumer International

Baumer Group · International Sales P.O. Box · Hummelstrasse 17 · CH-8501 Frauenfeld Phone +41 (0)52 728 1122 · Fax +41 (0)52 728 1144 sales@baumer.com · www.baumer.com

Find your local partner: www.baumer.com/worldwide