

CHECK VALVE



SW-200
Swing Check Valve
■ Size: 3/8" - 3" ■ 200 PSI
■ Body: CF8M



YSC-800
Y-Pattern Spring Check Valve
■ Size: 1/4" - 3" ■ 800 PSI
■ Body: CF8M



WC-100
Wafer Check Valve
■ Size: 1/2" - 12"
■ ANSI CL 150, 300
■ DIN PN 10 - 40
■ Body: CF8M



SLC-3
3-Piece Spring Loaded Check Valve
■ Size: 1/4" - 4" ■ 1000 PSI max.
■ Body: CF8M
■ Ends: Threaded, Socket Weld, Butt Weld

Dual Plate Wafer Type Check Valve

Size: 2" - 24"

Installation Dimensions: ■ ANSI 125-2500
■ PN 10-40
■ JIS 10K, 20K

VALVE MATERIALS

Body ASTM A129 Class B, A536 65-45-12

A216 WCB, CF8, CF8M, CF3M

Plate B584 C836, B148 C958,

A216 WCB, CF8, CF8M, CF3M

Seats NBR(BUNA-N), NEOPRENE, VITON

316 S/S overlay, 410 S/S overlay

Stellite overlay



FIG. DWC-1



FIG. DWC-2