


STAINLESS STEEL Y-TYPE GLOBE VALVE

Outside screw & Yoke bolted bonnet flanged ends

1/2" to 12", ANSI 150#, DIN PN 10/16, JIS 10K

Design Standard
Shell thickness ANSI B16.34
Face to face ANSI B16.10, JIS B2002
Flanges ANSI B16.5, DIN 2501, JIS B2210



STAINLESS STEEL CHECK VALVE

ANSI 150#, ANSI 300#, DIN PN 10/16, JIS 10K, JIS 20K

Size range

ANSI 150# / JIS 10K 1/2" to 24"
ANSI 300# / JIS 20K 1/2" to 12"
PN 10/16 1/2" to 12"

Design Standard

Shell wall thickness ANSI B16.34
Face to face ANSI B16.10, DIN 3202, JIS B2002
Flanges to ANSI B16.5, DIN 2501, JIS B2210



ANSI 150# / JIS 10K



ANSI 300# JIS 20K



DIN PN 10/16

STAINLESS STEEL LIFT TYPE CHECK VALVE

1/2" TO 16", ANSI 150#, JIS 10K

Design Standard
Shell thickness ANSI B16.34
Face to face ANSI B16.10, JIS B2002
Flanges ANSI B16.5, DIN 2501, JIS B2210

