


MARS HIGH PERFORMANCE FLANGED BALL VALVES



SERIES 90 
ANSI CLASS 150, PN16-40
Fire Safe Tested to API 607 4th Edition
Size: 1/2" - 4" Full Port
Body: CF8M / WCB, 1.4408 / GS-C25
Ball/Stem: 316 S.S. / 17-4PH
Seats: PTFE, RTFE, TFM1600
Face to Face: ANSI B16.10
EN 558-1, GR. 1/GR. 27
(DIN 3202-F1, F4/F5)
■ NACE MR - 0175 On Request



SERIES 90D 
ANSI CLASS 150, 300, PN16-40
Direct Mount Design
Fire Safe Tested to API 607 4th Edition
Size: 1/2" - 12" Full Port
Body: CF8M / WCB, 1.4408 / GS-C25
Ball/Stem: 316 S.S. / 17-4 PH
Seats: PTFE, RTFE, TFM1600
Face to Face: ANSI B16.10
EN 558-1, GR. 1/GR. 27
(DIN 3202-F1, F4/F5)
■ NACE MR - 0175 On Request



SERIES 96D 
ANSI CLASS 600
Direct Mount Design
Fire Safe Tested to API 607 4th Edition
Size: 1/2" - 4" Full Port
Body: CF8M / WCB,
Ball/Stem: 316 S.S. / 17-4 PH
Seats: PTFE, RTFE, TFM1600
Face to Face: ANSI B16.10
■ NACE MR - 0175 On Request



SERIES 91D
ANSI CLASS 150, 300
Direct Mount Design
Fire Safe Tested to API 607 4th Edition
Size: 1/2" - 6" Reduced Port
Body: CF8M / WCB
Ball/Stem: 316 S.S. / 17-4 PH
Seats: PTFE, RTFE, TFM1600
Face to Face: ANSI B16.10
■ NACE MR - 0175 On Request



SERIES 99 
PN 16-40, ANSI CLASS 150
Direct Mount Design
Fire Safe Design in Compliance with API 607
Size: 1/2" - 6" Full Port
Body: CF8M / WCB, 1.4408 / GS-C25
Ball/Stem: 316 S.S. / 17-4 PH
Seats: PTFE, RTFE, TFM1600
■ NACE MR - 0175 On Request