

SERIES 61

STAINLESS STEEL KNIFE GATE VALVE

2" – 24" ANSI 150#, DIN PN 10/16, JIS 5K/10K

- High-quality, full port design
- Compact, Low Profile
- Metal or Resilient Seat
- Precision-buffed stainless steel gate
- Manual, Gear Operator, Pneumatic or Electric Cylinder

Body: CF8M, CF8, CF3M

Knife: S.S. 316, S.S. 304, S.S. 304L, S.S. 316L

Seat: Metal, Teflon, VITON, EPDM

Packing: NON-ASB+PTFE, ASB, ASB+PTFE, TEFLON, NON ASBESTOS

Resilient Seat Material	Temperature
ASBESTOS + PTFE	-50°C ~ 550°C
VITON	-20°C ~ 250°C
TEFLON	-30°C ~ 150°C
NON ASBESTOS	-50°C ~ 550°C

★ Each valve is pressure tested for seat tightness, shell and packing integrity to check for reliability operation



FIG. 61M
Manual



FIG. 61P
Pneumatic



FIG. 61E
Electric Cylinder



FIG. 66B
2-Stage
Pneumatic



FIG. 66C
Manual-Pneumatic
Switchover

SERIES 62

CAST IRON KNIFE GATE VALVE

2" – 24" ANSI 150#, DIN PN 10/16, JIS 5K/10K

Body: FC, FCD, WCB

Knife: S.S. 316, S.S. 304,
S.S. 304L, S.S. 316L

Seat: Metal, Teflon, VITON, EPDM

Packing: NON-ASB+PTFE, ASB,
ASB+PTFE, TEFLON, NON
ASBESTOS




FIG. 62M
Manual



FIG. 62P
Pneumatic

